


L BEND BRACKET JACK

- Easy cranking 8 turns per inch
- Smooth, comfortable, ergonomic design
- Dependable vertical and side load capacity
- Operate in seconds with new pull-pin swivel release
- Tight tubing alignment guarantees against wobbling
- Powder coated outer tube and zinc plate inner tube




PASSED THE
3RD PARTY
LAB TEST
IN USA



Item No.	Lift Capacity	Lift	A Retracted	B Retracted	C	Type of Wind
701000	2,000 lbs	10"	11-1/4"	17"	N/A	Top
701076	2,000 lbs	15"	15"	20-1/4"	N/A	Top
701153	5,000 lbs	10"	11-1/4"	16-1/2"	N/A	Top
701155	5,000 lbs	15"	16-1/4"	21-1/2"	N/A	Top
701121	2,000 lbs	10"	11-1/4"	16-1/2"	N/A	Side
701122	2,000 lbs	15"	15"	22-1/2"	N/A	Side
701123	5,000 lbs	10"	11-1/4"	17-1/4"	N/A	Side
701126	5,000 lbs	15"	15-3/4"	21-1/4"	N/A	Side

TUBE MOUNT JACK

- Provide increased capacity for heavier tongue weights and greater side loads
- Rolled acme threads of the inner screw
- Easy cranking 8 turns per inch
- 5/8" diameter locking pin secures jacks in the vertical position for added support or in the storage position for ease of transport.



Item No.	Lift Capacity	Lift	A Retracted	B Retracted	C	Type of Wind
701081	2,000 lbs	10"	11-1/4"	16-1/2"	N/A	Top
701007	2,000 lbs	15"	16-1/4"	21-1/2"	N/A	Top
701086	5,000 lbs	10"	11-1/4"	16-1/2"	N/A	Top
701082	5,000 lbs	15"	16-1/4"	21-1/2"	N/A	Top
701009	2,000 lbs	10"	11-1/4"	16-1/2"	N/A	Side
701008	2,000 lbs	15"	16-1/4"	23-1/4"	N/A	Side
701124	5,000 lbs	10"	11-1/4"	17-1/4"	N/A	Side
701125	5,000 lbs	15"	15-3/4"	21-1/4"	N/A	Side